

S301E SERIES ELECTRICALLY ACTUATED BUTTERFLY VALVE

10 - 16 BAR Rated

Article no. WAFER PATTERN	Article no. LUGGED for flanges BS4504 - PN16		Size	Actuator Size
SIRWE040*	SIRLE040*		1/2"	HQ005
SIRWE050*	SIRLE050*		2"	HQ005
SIRWE065*	SIRLE065*		2 1/2"	HQ005
SIRWE080*	SIRLE080*		3"	HQ005
SIRWE100*	SIRLE100*	* Suffix with: A = 220v AC B = 110v AC	4"	HQ005
SIRWE125*	SIRLE125*		5"	HQ015
SIRWE150*	SIRLE150*		6"	HQ015
SIRWE200*	SIRLE200*		8"	HQ015
SIRWE250*	SIRLE250*		10"	HQ030
SIRWE300*	SIRLE300*		12"	HQ050
SIRWE040D	SIRLE040D	24v DC	1/2"	HQ005
SIRWE050D	SIRLE050D	24v DC	2"	HQ005
SIRWE065D	SIRLE065D	24v DC	2 1/2"	HQ005
SIRWE080D	SIRLE080D	24v DC	3"	HQ005
SIRWE100D	SIRLE100D	24v DC	4"	HQ005
SIRWE125D	SIRLE125D	24v DC	5"	HQ015
SIRWE150D	SIRLE150D	24v DC	6"	HQ015
SIRWE200D	SIRLE200D	24v DC	8"	HQ015
SIRWE250D	SIRLE250D	24v DC	10"	HQ030
SIRWE300D	SIRLE300D	24v DC	12"	HQ050



Wafer pattern



Lugged

ELECTRICALLY ACTUATED VALVES

Materials - Wafer

Body	Cast Iron GG25 Polyurethane Coated
Disc/shaft	316 Stainless Steel
Liner	EPDM (Nitril – On Request)
Temp. Range	+70°C
Flange Compatibility	BS4504 PN10/16 ANSI Class 150

Materials - Lugged

Body	Cast Iron GG25 Polyurethane Coated
Disc/shaft	316 Stainless Steel
Liner	EPDM (Nitril – On Request)
Temp. Range	+70°C
Flange Compatibility	BS4504 PN10/16

HQ005 Actuator dimensions- see page 34

HQ006 Actuator dimensions- see page 35

HQ008 - HQ-120 Actuator dimensions- see page 36

HQ200 - HQ-300 Actuator dimensions- see page 37

Wafer valve dimensions- see page 90

Lugged valve dimensions- see page 91