

FT260 SERIES SOFT SEATED HYDRAULIC CHECK VALVES



350 BAR Rated

Steel

0.35 BAR Spring Rated - Soft Seated suitable for gas

Article no.	Size BSP	Max Pressure BAR	Max Flow LPM
203002	1/4"	400	15
203003	3/8"	400	30
203004	1/2"	400	55
203005	3/4"	400	80
203006	1"	320	110



Steel

4.5 BAR Spring Rated - NOT Soft Seated

Article no.	Size BSP	Max Pressure BAR	Max Flow LPM
403002	1/4"	400	15
403003	3/8"	400	30
403004	1/2"	400	55
403005	3/4"	400	80
403006	1"	320	110

316 Stainless Steel

0.35 BAR Spring Rated - Soft Seated suitable for gas

Article no.	Size BSP	Max Pressure BAR	Max Flow LPM
203040	1/8"	400	10
203041	1/4"	400	15
203042	3/8"	400	30
203043	1/2"	400	55
203044	3/4"	400	80
303045	1"	320	110



Materials

Body	Steel 9Mn28K or 316 Stainless Steel
Check Valve	Steel Ball or 316 Stainless Steel
Check Guide	Nylon
Spring	Spring Steel AISI 302 or 316 Stainless Steel
Spring Rating	0.35 BAR or 4.5 BAR
Temp. Range	-20 TO +100°C
Thread	BSP Female

Dimensions (mm)

SIZE	B	C	CH	Weight kg
1/8"	8.5	41	16	0.054
1/4"	12.5	54	19	0.089
3/8"	13	65	24	0.175
1/2"	16	77	30	0.310
3/4"	20	88	36	0.450
1"	23	108.5	46	0.965

