



### Materials

Body	Steel
	316 Stainless Steel
Seal	NITRIL - Standard
	Others on Request
Temp. Range	NBR/Nitril -20 to 100°C
	Viton -20 to 200°C
	EPDM -40c to 150°C

# PRESSURE TEST POINTS

400 - 630 BAR Rated  
Test Point Connection M16 x 2

Connect and disconnect under full system pressure  
with built in thread seal

## Carbon Steel

Article no.	Connection	PN – BAR	Price £	Price €
20.10.47	M10 x 1	400	£14.10	€16.90
20.10.56	M12 x 1.5	630	£9.50	€11.40
20.10.76	M14 x 1.5	630	£13.70	€16.50
20.10.77	M16 x 1.5	630	£21.70	€26.10
20.10.73	G1/8"	400	£9.70	€11.70
20.10.66	G1/4"	630	£6.70	€8.00
20.10.58	G3/8"	630	£17.00	€20.40
20.10.12	G1/2"	630	£17.00	€20.40
20.10.59	1/4" NPT	630	£9.50	€11.40

## Stainless Steel

Article no.	Connection	PN – BAR	Price £	Price €
20.08.73	G1/8"	400	£105.70	€126.80
20.08.66	G1/4"	630	£65.00	€77.90
20.08.58	G3/8"	630	£113.80	€136.60
20.08.12	G1/2"	630	£68.30	€81.90
20.08.59	1/4" NPT	630	£82.30	€98.80

## Dimensions

T	h1	h2	SW
M10 x 1	38	9.8	17
M12 x 1.5	37	12	18
M14 x 1.5	37	12	19
M16 x 1.5	37	12	22
g 1/8"	39	8	17
g 1/4"	37	12	22
g 3/8"	37	13	22
g 1/2"	39	14	27
1/4" npt	35	15	17

