



3 WAY ELECTRICALLY ACTUATED STAINLESS STEEL BALL VALVE 'L' & 'T' BORE

1,000 PSI Rated - 1/4" to 2"

Article no. L bore	Article no. T bore		Size	Actuator Size	Price £	Price €
399061*	399071*		1/4"	HQ005	£561.90	€674.20
399062*	399072*		3/8"	HQ005	£561.90	€674.20
399063*	399073*		1/2"	HQ005	£561.90	€674.20
399064*	399074*	* Suffix with: A = 220v AC	3/4"	HQ005	£590.20	€708.20
399065*	399075*	B = 110v AC	1"	HQ005	£647.00	€776.40
399066*	399076*	Others on request	1 1/4"	HQ005	£745.10	€894.10
399067*	399077*		1 1/2"	HQ005	£943.10	€1,131.70
399068*	399078*		2"	HQ006	£1,367.20	€1,640.60
399061D	399071D	24v DC	1/4"	HQ005	£584.30	€701.10
399062D	399072D	24v DC	3/8"	HQ005	£584.30	€701.10
399063D	399073D	24v DC	1/2"	HQ005	£584.30	€701.10
399064D	399074D	24v DC	3/4"	HQ005	£612.60	€735.10
399065D	399075D	24v DC	1"	HQ005	£669.40	€803.30
399066D	399076D	24v DC	1 1/4"	HQ005	£767.50	€921.00
399067D	399077D	24v DC	1 1/2"	HQ005	£965.50	€1,158.60
399068D	399078D	24v DC	2"	HQ006	£1,389.60	€1,667.50

Materials

Body	CF8M - 316 Stainless Steel
Ball	316 Stainless Steel
Stem Seal	PTFE
Ball Seal	PTFE
Temp. Range	+70°C*

Specifications - HQ005 Actuator

Enclosure	Weatherproof enclosure IP67
Power supply	85 - 265 VAC 1 ph, 50/60 Hz 24 VAC/DC
Duty cycle	S4: 70% (average load of 80% Max. torque) S2: 50% (average load of 80% Max. torque)
Motor	BLDC motor
Limit switches	2 x open/close, SPDT, 250 V ac 10 A rating
Additional limit switches	2 x open/close, SPDT, 250 V ac 10 A rating
Anti-condensation board	2 W
Manual override	Manual Handwheel
Cable entries	Standard: 2 x M20
Movement angle	320 ± 10° (0 - 330°)
Ambient temperature	-20 to +80 °C

Dimensions (mm) - HQ005 Actuator

