

Solenoid Operated Directional Control Valves

Product Description

Solenoid operated directional control valve.
Directing flow within a hydraulic circuit to achieve flow path change.

Technical

CETOP 3 (NG 6)
CETOP 5 (NG 10)
Installationary interchangeable with all CETOP standard valves.
DSG - 01
Up to 100Lpm at 350Bar
DSG - 03
Up to 120Lpm at 315Bar

Associated Products

Sub plates, manifolds and modular valves.
For larger flows, up to 1100Lpm, the CETOP 8 and 10 range of solenoid piloted directional control valves.

CETOP MOUNTED VALVES



		DSG - $\begin{matrix} \diagup 01 \\ \diagdown 03 \end{matrix}$	Spool Type (see below)	Voltage (see below)	- N - Design		
THREE POSITIONS	SPRING CENTRED		3C2	A120	110 VAC		
			3C3	A240	240 VAC		
			3C4	D24	24 VDC		
			3C40	D12	12 VDC		
			3C5				
			3C60				
			3C9				
			3C10				
			3C11				
			3C12				
		TWO POSITIONS	NO-SPRING OFFSET		2D2		
			SPRING OFFSET		2B2		
	2B3						
	2B8						

DSG-01-2B*-*****-N
DSG-01-3C*-*****-N
DSG-03-2B*-*****-N
DSG-03-3C*-*****-N

Example valve code:
DSG-03-3C60-D24-N-50