# SERIES: DF

#### **Carbon Steel**

Flat face couplings specifically designed to measure the internal pressure of hydraulic circuits. Male part to be mounted on the hydraulic line and female part to be connected to gauge instruments. ISO 15171-1 interchange.

## **Technical Features**

Material Steel Seals NBR

Working temperatures -25° C ... +125° C
Surface treatment MATE 500 (CrIII)
Series Interchange ISO 15171-1
Valve Type Flat face
Connection Push to Connect
Disconnection Sleeve Retraction
Connection Under Pressure Not Allowed

Application Agriculture, Construction, Industrial, Vehicle

Article no.	Description	Price £	Price €
343474	Flat Face Female 06 Body 1/8" NPTF	£18.80	€18.80
343475	Flat Face Female 06 Body 1/4" NPTF	£18.80	€18.80
343476	Flat Face Female 06 Body 1/4" NPTM	£18.80	€18.80
343478	Flat Face Male 06 Body 1/8" NPTF	£7.70	€8.00
343479	Flat Face Male 06 Body 1/4" NPTF	£7.70	€8.00
343477	Flat Face Male 06 Body 1/4" NPTM	£7.70	€8.00

#### **Technical Data**

Series	DN	DN	Flow	Working	Burst	Spillage		
		ISO 4397	Rate	Pressure	Connected	Female	Male	
	Inch	mm	l/min	Bar	Bar	Bar	Bar	ml
DF	1/4	6.3	2	470	1800	1500	1900	0.01

The indicated pressure ratings only apply to the coupling itself and depend on the connection type.

# **Dimensions - Female**

		Thread	Standard	Thread	Part Number	<u> </u>	-	D	1	HE	X1
		Type				(L1 + T	hread)				
6.3	1/4"	01/ NPTF	ANSI B1.20.3	1/4" NPTF MALE	DF 04-1/14NPT F	56mm	2.2"	24mm	0.94"	21mm	0.83"
6.3	1/4"	F NPTF	ANSI B1.20.3	NPTF 1/8" FEMALE	DF 04-18NPT F	42mm	1.65"	24mm	0.94"	21mm	0.83"
6.3	1/4"	F NPTF	ANSI B1.20.3	NPTF 1/4" FEMALE	DF 04-14NPT F	50mm	1.97"	24mm	0.94"	21mm	0.83"

## Dimensions - Male

		Thread Type	Standard	Thread	Part Number	(L1 + T	L Thread)	С	)1	D	3	HE	X1
mm	inch					mm	inch	mm	inch	mm	inch	mm	inch
6.3	1/4"	F NPTF	ANSI B1.20.3	NPTF 1/8" FEMALE	DF 04-18NPT M	36.1	1.42"	19	0.75"	12.55	0.49	19	0.75
6.3	1/4"	F NPTF	ANSI B1.20.3	NPTF 1/4" FEMALE	DF 04-14NPT M	40	1.57"	21	0.83"	12.55	0.49	19	0.75
6.3	1/4"	01/ NPTF	ANSI B1.20.3	1/4" NPTF MALE	DF 04-1/14NPTM	41.1	1.62"	21	0.83"	12.55	0.49	19	0.75

# SERIES: **DF - DUST PROTECTION**

Series	Size	Material	Dust cap for male tip	Price £	Price €
DF	04	Plastic (Green - Standard)	TFDF 04	£1.90	€2.00

Original FASTER  $^{\otimes}$  dust protections keep the mating surfaces clean and protect the latching elements when the coupling halves are disconnected.

Protections for DF couplings are made of oil proof PVC which endures temperatures ranging from -30°C to +100°C.





Male thread for Female coupling



