
In line single-acting flow control valves

FT 2257/5

Single-acting flow control valves available from 1/8" to 2" BSPP size, max.working pressure 400 Bar / 320 Bar, adjustable oil flow rate from 0,5 to 200 Lt./min. (depending on the size)

Single-acting control
In line or panel mounting
Stainless Steel AISI 316
Attacchi: F - F Female - Female





Technical information

Technical description

The valves FT 2257/5 have function of regulating and, if necessary, to shut-off the flow in one direction, allowing a free flow in the opposite direction. Appreciated for their aesthetic characteristics that indulge positively the constructive directions of the equipments on which they are installed, they are also a reliable solution. The proper dimensioning has made possible to obtain, in a little space, a great mechanic resistance of the components. The spring in high-resistance material is housed in such a way that it does not close as a pack during the opening of the taper single-acting shutter valve. Like all the valves of the series FT 2257 they ensure: • efficient metallic sealing; • flow linearity at the opening; • accurate control for a wide range of flow rate, thanks to the double reference system • wide range of the flow rate control; • impossibility for the needle to leave its seat even in the max. opening position; • stable positioning thanks to a screw inside the knob; • quickness in panel mounting (the ring nuts (G) are supplied on request). The check valve is set to 0,5 bar.

Materials


CORPO VALVOLA / BODY VALVE	Acciaio INOX / Stainless Steel AISI 316
SPILLO DI REGOLAZIONE / ADJUSTING NEEDLE	Acciaio INOX / Stainless Steel AISI 316
GUARNIZIONI / GASKETS	FPM
ANELLI ANTIESTRUSIONE / ANTIEXTRUSION RINGS	PTFE
VALVOLA DI RITEGNO / CHECK VALVE	Acciaio INOX / Stainless Steel AISI 316
MOLLA / SPRING	Acciaio INOX / Stainless Steel AISI 316
FONDELLO FILETTATO / THREADED LOCKING RING	Acciaio INOX / Stainless Steel AISI 316
MANOPOLA TIPO MA - RA / KNOB TYPE MA - RA	Alluminio/Aluminum GD AlSi12- UNI EN AB 46100
MANOPOLA TIPO MP / KNOB TYPE MP	ABS


Technical data

TIPO / TYPE	PRESSIONE ESERCIZIO BAR / WORKING PRESSURE BAR	MIN. PRESSIONE SCOPPIO BAR / MIN. BURSTING PRESSURE BAR	TEMPERATURA ESERCIZIO / WORKING TEMPERATURE	GRADO DI FILTRAZIONE µm / FILTRATION GRADE µm
18	400	1600	-20°C/+130°C	25
14	400	1600	-20°C/+130°C	25
38	400	1600	-20°C/+130°C	25
12	400	1600	-20°C/+130°C	25
34	400	1600	-20°C/+130°C	25
100	320	1300	-20°C/+130°C	25
114	320	1300	-20°C/+130°C	25
112	320	1300	-20°C/+130°C	25
200	320	1300	-20°C/+130°C	25


Dimensional tables and drawings

TIPO / TYPE	A UNI 338	B	C	D	E	ØF	ØF1	G	H	CH	PESO / WEIGHT KG
18	1/8" G	8,5	50	59	64	22	40	13,5	M17x1	16	0,130
14	1/4" G	12,5	66	71	78	27	50	17	M20x1	20	0,250
38	3/8" G	12,5	79	84	93	33	70	19,5	M25x1,5	25	0,500
12	1/2" G	15,5	94.5	97	107	38	80	21	M30x1,5	30	0,750
34	3/4" G	17	115	120,5	132,5	47	100	26,5	M40x1,5	40	1,600
100	1" G	20	138.5	151,5	167,5	58	120	35	M50x1,5	50	3,050
114	1 1/4" G	22	157	156,5	172,5	58	120	35	M50x1,5	55	3,750
112	1 1/2" G	24	190	167	181	58	120	35	M55x2	65	5,760
200	2" G	27	228	188	202	108	/	44	M65x2	75	10,000







Flow rate curves




a







FT 2257/5 - 12




FT 2257/5-34




FT 2257/5 - 100




FT 2257/5 - 114




FT 2257/5 - 112



FT 2257/5 - 200




FT 2257/5 - PORTATA A FLUSSO LIBERO / FREE FLOW
Caduta di Pressione - Pressure drop
Δp - bar
Portata Olio / Oil flow - l/min
18
14
38
12
34
100
114
112
200
Olio / Oil = 4 °E - 50°C
TOGNELLA
0
5
10
15
20
25
0
100
200
300
400
500
600
700
800
900
1000